

Biostrength® 280

Transparent Impact Modifier

PRODUCT DESCRIPTION

Biostrength® 280 impact modifier is an acrylic core shell impact modifier designed to increase toughness of polylactic acid (PLA) while maintaining clarity.


TYPICAL PHYSICAL PROPERTIES*

Physical Form	Powder
Bulk Density	0.47 g/cc
Particle Size	15% Max on 50 Mesh
Percent Volatiles	1.0% Max

*Typical properties not to be construed as specifications

PRODUCT BENEFITS

Haze 15 mil sheet



PRODUCT BENEFITS

Impact Improvement

Biostrength® 280 impact modifier increases impact strength of PLA extruded, calendered, blow molded, thermoformed and 3D printing articles.

Biostrength® 280 impact modifier maintains low haze in PLA at recommended use levels.

SUGGESTIONS FOR USE


Biostrength® 280 impact modifier is recommended for use in PLA applications that require toughness and high transparency. Typical use levels range from 2% to 6% by weight. Blends of Biostrength® 280 impact modifier with PLA can be processed in the same equipment and under the same processing conditions recommended for PLA.

Prospective clients should evaluate Biostrength® 280 impact modifier in their own laboratories to establish optimum conditions for use in their processes and applications. Arkema's Technical Service Team is available to discuss your application requirements, provide formulation guidance and laboratory testing as needed. The Technical Service Team can also provide the current clearances and limitations for use in food packaging applications.

PACKAGING

Biostrength® 280 impact modifier is packaged in 18 kg bags.

Gardner Impact 15 mil sheet



ENVIRONMENTAL AND SAFETY INFORMATION

Before handling this material, read and understand the Safety Data Sheet (SDS) for additional information on handling, storage, and disposal of the product to ensure the health of users, the safety of facilities, and the protection of the environment. The SDS is available on our website www.arkema.com or upon request at our Customer Service Department. Arkema believes strongly in Responsible Care® as a public commitment.

MORE TECHNICAL INFORMATION AVAILABLE

Ask your Arkema account manager for further information on high quality Arkema additives for use in PVC, PC, PBT, ABS, PLA, epoxies, (meth)-acrylics, and other thermoplastic or thermosetting systems. Arkema produces a full line of impact modifiers and processing aids. In addition, Arkema's Technical Service staff is also available to assist compounders and processors with formulation and processing recommendations.

Durastrength® Impact Modifiers

Durastrength® acrylic impact modifiers deliver outstanding impact characteristics for outdoor durable applications in PVC, engineering resins and thermosets.

Plastistrength® Process Aids

Plastistrength® process aids offer producers a complete line of melt strengtheners and metal release agents for PVC and engineering resins. Plastistrength® process aids can improve fusion, surging, and aesthetics.

Biostrength® Additives

Biostrength® impact modifiers are designed to improve properties and enhance processability of polylactic acid (PLA) and other biopolymer compounds.

FOR MORE INFORMATION CONTACT

Please contact your local account manager, our headquarters, or our R&D centers:

Global Headquarters

Arkema
Arkema Coating Resins
LIGHTWELL Building
51 Esplanade du Général de Gaulle
CS 10478 - 92907 Paris La Défense cedex
France
Tel: +33 (0)1 49 00 80 80
plasticadditives.arkema.com/en/contact/

US Headquarters

Arkema Inc.
Arkema Coating Resins
410 Gregson Dr.
Cary, NC 27511
Tel: +1 (877) 331-6696
plasticadditives.arkema.com/en/contact/

US R&D Center

Arkema Inc.
900 1st Avenue
King of Prussia, PA 19406
Tel: +1 (610) 878-6500
plasticadditives.arkema.com/en/contact/

Visit
plastic.additives.arkema.com



ASK QUESTIONS
TO OUR EXPERTS



LIBRARY
DOCUMENTS
WEBINARS



WEB SERVICES
TDS
SAMPLING



INTERACTIVE
PRODUCT FINDERS
& BROCHURES

Plastistrength® is a registered trademark of Arkema. Biostrength® and Durastrength® are registered trademarks of Arkema Inc. Responsible Care® is a registered trademark of the American Chemistry Council Inc. 2026 Arkema Inc. All rights reserved.

Please consult Arkema's disclaimer regarding the use of our products on
<http://www.arkema.com/en/products/product-safety/disclaimer/>

ARKEMA

plasticadditives.arkema.com